# SPRAYON PRODUCTS (PTY) LTD

# **MATERIAL SAFETY DATA SHEET**

Date issued 20/07/2009

# **BC1: BURNISHING COMPOUND**

DNM



### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product CodeBC1Product NameBURNISHING COMPOUNDDNMCAS No.Not applicableEC NoNot applicableUN No1263

Company Name Sprayon Products

222 2<sup>nd</sup> Street Wynberg

Emergency contact no: 011-440-2202

# **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Class PAINT or PAINT RELATED

Classification - Xn R Phrases R10,65,36/38 S Phrases S02,13,26,43A,62

Comment OEL Type: Mixture - See tables in Sections 2 and 8

% m/m EC Labels CAS No. EC No.

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

### **SECTION 3. HAZARDS IDENTIFICATION**

SAPMA Health Rating 2-MODERATE - Temporary or minor injury possible even if treatment given

Inhalation Irritating.

Skin Highly irritating. Risk of dermatitis. May be absorbed through intact skin.

**Eyes** Irritating - may cause damage if not given prompt attention.

**Ingestion** Harmful. May cause lung damage if swallowed.

No carcinogenic, mutagenic or genetic effects established

May have short term environmental effects. Contain, monitor & remove

### **SECTION 4. FIRST AID MEASURES**

**Inhalation** Move to fresh air.

**Skin** Drench with water. Remove contaminated clothing. Use a skin cleaner. In severe cases refer to Doctor.

**Eyes** Rinse well with water and seek medical advice if discomfort persists. **Ingestion** DO NOT INDUCE VOMITING. Get immediate medical attention.

# **SECTION 5. FIRE FIGHTING MEASURES**

Flammable with toxic fumes. Containers liable to burst in a fire.

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

### SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Keep out of drains and sewers

### SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.

No open flames. No smoking.

Store containers with due care in case of fire.

Subject to local bylaws

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS No. OEL OEL STOEL OEL OEL (mg/m3) (ppm) (mg/m3) (PPM) Type

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

WHITE SPIRIT (WS3) 64742-88-7 575 100 720 125 RL TETRAHYDRO-1,4-OXAZINE, MORPHOLINE 110-91-8 71.0 20.0 RL S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SAPMA Rating 2-H-E PPE : Respirator and Eye protection

Inhalation In case of insufficient ventilation, use suitable respiratory protection.

Skin AVOID CONTACT. Use impervious gloves, apron and boots.

Eyes Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves.

**Ingestion** Observe the rules of hygiene. Wash before eating or drinking.

OEL Type: Mixture - See tables in Sections 2 and 8



### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance<br/>pHWater based dispersion<br/>6-8Odour<br/>Boiling PointTypical<br/>>35°CFlash Point>23°C(derived)Water solubilitymiscible

### **SECTION 10. STABILITY AND REACTIVITY**

Stable under normal conditions

No reaction with fire-fighting water

# **SECTION 11. TOXICOLOGICAL INFORMATION**

No carcinogenic, mutagenic or genetic effects established LD50 Oral: >500 mg (derived)

#### SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove

### **SECTION 13. DISPOSAL INFORMATION**

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

# **SECTION 14. TRANSPORT INFORMATION**

UN Number 1263

Shipping Name PAINT or PAINT RELATED MATERIAL

IMO Class 3.3 Packing Group III

Action Code 127 HazChem 3[Y] Kemler Code 30



### **SECTION 15. REGULATORY INFORMATION**

EC no.: n/a

- Xn R Phrases R10,65,36/38 S Phrases S02,13,26,43A,62

R10 - Flammable

R65 - Harmful: May cause lung damage if swallowed.

R36/38 - Irritating to eyes and skin

S2 - Keep out of reach of children. (Retail sales items)

S13 - Keep away from food, drink and animal feeding stuffs

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S43A - In case of fire, use water fog, foam or powder - Do not use water jets!

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.



# **SECTION 16. OTHER INFORMATION**

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue: 20/07/2009 Date of analysis: 20/07/2009)